



2-7Y

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 50V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material:PBT,UL94V-0

编 号	尺寸 (mm)	
	A	B
A1257H-2P	1.25	3.75
A1257H-3P	2.50	5.00
A1257H-4P	3.75	6.25
A1257H-5P	5.00	7.50
A1257H-6P	6.25	8.75
A1257H-7P	7.50	10.00
A1257H-8P	8.75	11.25
A1257H-9P	10.00	12.50
A1257H-10P	11.25	13.75
A1257H-11P	12.50	15.00
A1257H-12P	13.75	16.25
A1257H-15P	17.50	20.00

GENERAL TOLERANCE		制图	料号		版本
X.±0.25	X.'±2'	DRAWING	PART NO.	A1257H-XXP	REV.
.X±0.20	.X'±1'	审核	品名		A
.XX±0.15	.XX'±0.5'	CHECK	客户料号		1/1
.XXX±0.10	.XXX'±0.5'	核准	CUTM. NO.		
		APPRONAL			
		单位	深圳市德益连接器有限公司		
		UNITS	SHENZHEN DEYI CONNECTORS CO., LTD.		
		MM	比例	1:1	
			SCALE		